

CANIS GO 410

REVERSE

Our entry-level Canis GO 410 Reverse light is as good as it gets. While it is lighter than the original, the operational lumen output is just as high. Best suited to construction, forestry, agriculture, and material handling, the Canis Go 410 Reverse has a round form factor and pedestal mounting, it produces zero emissions (EMC CISPR 25 class 5) and its light output is 1000 lumens.

Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.



TECHNICAL DATA

Theoretical Lumens Output	1600 lm	Vibration	8Grms 24-2000Hz
Operational Lumens Output	1000 lm	Lens	Grilamid® (registered trademark of EMS-GRIVORY)
Colour Temperature	5000 K	Body / Housing	Aluminium
Nominal Voltage DC	12 - 24 V	Weight	0.6 kg
Input Voltage DC	9 - 16 V 18 - 32 V	IP Rating	IP68, IP6K9K
Power Consumption	16 W	Salt Spray Test	ISO 9227 240H
Nominal Current at	24V=0.6A, 12V=1.05A	EMC	CISPR 25 Class 5, EN12895, ISO 13766, ISO 14982, ISO 7637-2, R10
Connector	Built-in Deutsch DT-2 (2-pin)		
Mount	Single Bolt M8	Operating Temperatures	-40°C... +85°C (Overheat protected)
Shock	60G	Part Numbers	Reverse: 988-501B

CONNECTORS



Built-in Deutsch DT-2 (2-pin)


KEY FEATURES

- Reverse light (ECE R23)
- Operational lumens output: 1000lm
- Pure performance in a compact design

LIGHT PATTERNS

Canis GO 410 R 1000lm

Reverse



DRAWINGS

