

SCORPIUS N4407

QD

NORDIC LIGHTS® Scorpius N4407 QD work light offers a sharp pencil beam and two other light pattern options: high beam and Glare-Free. This LED work light is equipped with the revolutionizing QUAKE dampening system, taking protection against vibration and shock to a whole new level. The Scorpius N4407 QD is suitable for harsh conditions and a range of applications.



Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

Theoretical Lumens Output	5600 lm	Vibration	20Grms 24-2000Hz, 4.65Grms 12-2000Hz
Operational Lumens Output	3500 lm	Lens	PC / Glass
Colour Temperature	5700 K	Body / Housing	Aluminum
Nominal Voltage DC	12 - 24 V	Weight	1.6 kg
Input Voltage DC	9 - 32 V	IP Rating	IP68, IP6K9K, SAE J1455
Power Consumption	55 W	Salt Spray Test	ISO 9227 240H
Nominal Current at	24V=2.2A, 12V=4.6A	EMC	CISPR 25 Class 3, ISO 13766, ISO 14982, ISO 7637-2
Connector	Built-in Deutsch DT-2 (2-pin)	Operating Temperatures	-40°C... +85°C (Overheat protected)
Mount	Single Bolt M10	Part Numbers	Glare-Free: 984-526B, High Beam: 984-503, Pencil Beam: 984-502
Shock	60G		

CONNECTORS




Built-in Deutsch DT-2 (2-pin)


KEY FEATURES

- QUAKE dampening system
- Operational lumens output: 3500lm
- For extremely harsh conditions

LIGHT PATTERNS



N4407 QD, N4408, 3500lm
Glare-Free



DRAWINGS

